

**1/4"**  
Diameter

The 1/4" rod is designed for long spans where rigidity is needed to cover the distance.

Minimum Bend Radius: 6"

Tensile/Pull Strength: 750-lbs

1/4" Glow Rod Kits	Total Rod Length	Packaged Kit Length	Part Number
Three 6' X 1/4" Rods, Two 3' X 1/4" Rods One Bullet Nose with Eyelet, One Hook	24'	6'	7-36-23T
Six 3' X 1/4" Rods One Bullet Nose with Eyelet, One Hook	18'	3'	7-63T
Three 4' X 1/4" Rods One Bullet Nose with Eyelet, One Hook	12'	4'	7-34T
One 3' X 1/4" Replacement Rod with Male and Female Ferrules	3'	*	7-3
One 6' X 1/4" Replacement Rod with Male and Female Ferrules	6'	*	7-6

*\* Single rods are shipped with hanging tag, not in clear plastic kit tube*



7-36-23T



7-63T



Point of Sale Packaging for Easy Display and Product Visibility

**3/16"**  
Diameter

The more flexible 3/16" rod is preferred for short runs or where space is more limited.

Minimum Bend Radius: 4"

Tensile/Pull Strength: 500-lbs

3/16" Glow Rod Kits	Total Rod Length	Packaged Kit Length	Part Number
Four 5' X 3/16" Rods One Bullet Nose with Eyelet, One Hook	20'	5'	7S-45T
Seven 18" X 3/16" Rods One Bullet Nose with Eyelet, One Hook	10.5'	18"	7S-718T
One 5' X 3/16" Replacement Rod with Male and Female Ferrules	5'	*	7S-5

*\* Single rods are shipped with hanging tag, not in clear plastic kit tube*



7S-45T



7S-718T

Convenient 18" kit length for toolboxes.

**5/32"**  
Diameter

The smallest diameter rod in Jameson's line offers extreme flexibility while maintaining high strength.

Ideal for security and alarm, home theater, CATV and satellite installation.

Minimum Bend Radius: 3.5"

Tensile/Pull Strength: 500-lbs

5/32" Glow Rod Kits	Total Rod Length	Packaged Kit Length	Part Number
Three 6' X 5/32" Rods One Bullet Nose with Eyelet, One Hook	18'	6'	7SS-36T
One 6' X 5/32" Rod with Permanently Mounted Bullet Nose with Eyelet On Each End of Rod	6'	*	7SS-6

*\* Single rods are shipped with hanging tag, not in clear plastic kit tube*



7SS-6



7SS-36T

Permanently mounted bullet nose on each end.

